



MINI DOCK



RETURN OF THE PORTS

The Thunderbolt™ 3 mini Docks provide the easiest and most affordable way of bringing back your laptop's ports. Thunderbolt™ 3 users can re-connect with their legacy devices in the most convenient way possible.

THUNDERBOLT 3


The Thunderbolt™ 3 mini Docks provide the easiest and most affordable way of bringing back your laptop's ports. Thunderbolt™ 3 users can re-connect with their legacy devices in the most convenient way possible.

DUAL 4K DISPLAYS


The mini Docks offer the easiest way to connect dual 4K 60Hz monitors to your Thunderbolt 3 laptop in either mirrored or extended modes.

HIGHLIGHTS

- Compliant to the power budget of 15W of down-streaming Thunderbolt port, assure all I/O ports working normally under sufficient power consumption
- Bus-powered
- Thermal dissipation verified
- Aluminum housing, compact & stylish
- Plug & Play, no driver needed
- High portability
- macOS & Windows compatible



DUAL DISPLAYPORT 1.2



DUAL HDMI 2.0

CALDIGIT MINI DOCK VS GENERAL USB-C HUBS

- Thunderbolt 3 specification, up to 40 Gb/s throughput, highly elevate the performance of workflows
- Thunderbolt 3 certified, it has passed strict validation tests
- Fully compliant to the Thunderbolt 3 Type-C Power budget design, free of power insufficiency & thermal issues
- Assure dual 4k 60Hz displays, no worry about green display or no video output issues
- Aluminium housing, compact design with high efficiency on heat dissipation
- High CP value product



TECHNICAL SPECIFICATIONS

CalDigit mini Dock Dual DisplayPort

Interface

- 1 x Thunderbolt 3 (40Gb/s)
- 2 x DisplayPort 1.2 (4096x2160 60Hz)
- 1 x USB 3.0 (5Gb/s)
- 1 x Gigabit Ethernet (RJ45)

In the Box

- 1 x CalDigit Thunderbolt 3 mini Dock - HDMI 2.0

System Requirements

- Thunderbolt 3 computers
- mac OS 10.12 or later
- Windows 10 or later

Environment

0°C ~ 35°C (32°F ~ 95°F)

Dimensions and Weight

- Height: 0.74 in (18.8 mm)
- Width: 4.88 in (124 mm)
- Depth: 2.56 in (65.0 mm)
- Weight: 0.3 lbs (0.14 kgs)

CalDigit mini Dock Dual HDMI

Interface

- 1 x Thunderbolt 3 (40Gb/s)
- 2 x HDMI 2.0 (3840x2160 60Hz or 4096x2160 60Hz)
- 1 x USB 3.0 (5Gb/s)
- 1 x USB 2.0 (480Mb/s)
- 1 x Gigabit Ethernet (RJ45)

In the Box

- 1 x CalDigit Thunderbolt 3 mini Dock - Dual DisplayPort

System Requirements

- Thunderbolt 3 computers
- mac OS 10.12 or later
- Windows 10 or later

Environment

0°C ~ 35°C (32°F ~ 95°F)

Dimensions and Weight

- Height: 0.74 in (18.8 mm)
- Width: 4.88 in (124 mm)
- Depth: 2.56 in (65.0 mm)



United States

CalDigit Inc
1941 E. Miraloma Ave. Ste. B
Placentia, CA 92870-6770
United States

Sales@CalDigit.com
+1 (714) 572-9889

UK & Europe

CalDigit UK LTD
Unit 3 Glenmore Business Centre,
Witney, OXON, OX29
0AA, United Kingdom

EUSales@CalDigit.com
+44 (0) 1993-700-972

Japan

Ayala Design Co., Ltd.
Sato Bld. 301,
1-21 Matsubara-cho, Kagoshima-Shi,
Kagoshima, 892-0833 Japan

Japan@CalDigit.com
+81 (50) 3136-5168

Asia

Castle Rock Inc.
3F, No.880, ZhengZhong Road
Zhonghe Dist., New Taipei City 23586,
Taiwan, R.O.C

Asia@CalDigit.com
+886 (2) 2226-0966