





### Expanding Thunderbolt<sup>™</sup> 3 Based Networks

Lightning fast performance is here! The Connect 10G Ethernet Adapter lets users with Thunderbolt<sup>™</sup> 3 enabled computers enjoy connections of up to 10Gb/s and enable connections to a server or Local Area Network up to 100 meters distance! It's the perfect solution to boost Enterprise SMB, Studio, Gaming and Home Networking.



The Connect 10G offers 10x the performance of a regular Ethernet port found on most computers. Transfer files faster and more efficiently than ever!



Fast networking is no longer confined to desktop computers. Any Thunderbolt<sup>™</sup> 3 laptop can benefit from a shared network.



The beauty of LAN-based networks is that you can transfer files over distances up to 100 meters. This makes the Connect 10G ideal for shared storage environments

# Wake-On-LAN(WoL)

With the Wake-On-LAN function, you can wake up your connected computer remotely to access your files from anywhere.

# Audio Video Bridging(AVB)

Audio and video are transferred in real time over the Ethernet port





# High speed connection to a shared storage environment

The Connect 10G enables smooth connections to NAS networks to transfer files and data faster than ever, allowing easier file access and more efficient collaboration.

### NBASE-T & Ethernet Cable compatibility

	Connect 10G Compatibility	Max. Transmission Speed	NBASE-T	Speed	Max.	Cable reg.	Cable rating
Cat 3	$\checkmark$	10Mbps	NDASE 1	(Mbit/s)	Distance(m)	cable reg.	(MHz)
Cat 5	$\checkmark$	100Mbps	100BASE-TX	100	100	Cat 5	100
Cat 5e	$\checkmark$	1Gbps	1000BASE-T	1,000	100	Cat 5e	100
Cat 6	$\checkmark$	1Gbps	2.5GBASE-T	2,500	100	Cat 5e	100
Cat 6a	$\checkmark$	10Gbps	5GBASE-T	5,000	100	Cat 6	250
Cat 7	$\checkmark$	10Gbps	10GBASE-T	10,000	100	Cat 6a	500

#### Specifications

Interface	1x Thunderbolt™ 3 (Type-C) Port 1x RJ45 10Gbps Ethernet Port				
System Requirements	Thunderbolt™ 3 Computer Windows (10 or higher) macOS (version 10.13.6 or higher)				
LED Indicators	Dual color Speed LED Single color Link/Act LED				
Advanced	IEEE 802.3an/bz standard Audio Video Bridging (AVB) Wake-On-Lan (WoL) Jumbo Frames: Windows up to 16 Kbytes macOS up to 9 Kbytes				
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)				
Power Supply	Bus-powered Operation - No Power Adapter Required				
Dimensions and Weight	97.4 L x 71 W x 43 H mm; Weight: 0.35 Kgs 3.83 L x 2.79 W x 1.69 H inch; Weight: 0.77 lbs				
In the box	1x Connect 10G; 1x Thunderbolt™ 3 cable (0.5m) 1x Quick Start Guide; 1x Support Card				



# Aluminum Chassis

The aluminum-build chassis ensures that the unit stays cool and remains quiet.





FBUS